



WSH 826S

鋼纜直徑 (mm)	拉斷負荷						(參考) 概算 單位質量 kg/m
	正常撚法						
	無鍍鋅 · 鍍鋅						
	1770 N/mm ² (180 kgf/mm ²)		1960 N/mm ² (200 kgf/mm ²)		2160 N/mm ² (220 kgf/mm ²)		
	kN	{tf}	kN	{tf}	kN	{tf}	
10	78.4	{8.9}	86.8	{8.9}	93.7	{9.6}	0.453
11	94.8	{10.7}	105	{10.7}	113	{11.5}	0.548
12	113	{12.8}	125	{12.8}	135	{13.8}	0.653
13	134	{15.1}	148	{15.1}	158	{16.1}	0.766
14	154	{17.4}	171	{17.4}	184	{18.7}	0.888
15	177	{20.0}	196	{20.0}	211	{21.5}	1.02
16	202	{22.9}	224	{22.9}	240	{24.5}	1.16
17	226	{25.5}	250	{25.5}	271	{27.6}	1.31
18	255	{28.8}	282	{28.8}	304	{31.0}	1.47
19	284	{32.0}	314	{32.0}	338	{34.5}	1.64
20	314	{35.5}	348	{35.5}	375	{38.2}	1.81
22	383	{43.3}	424	{43.3}	454	{46.3}	2.19
24	455	{51.4}	504	{51.4}	540	{55.1}	2.61
25	494	{55.8}	547	{55.8}	586	{59.1}	2.83
26	537	{60.7}	595	{60.7}	634	{64.6}	3.06
28	617	{69.7}	683	{69.7}	735	{74.9}	3.55
30	709	{80.1}	785	{80.1}	844	{86.0}	4.07
32	813	{91.8}	900	{91.8}	----	----	4.63
34	921	{104}	1020	{104}	----	----	5.24
36	1020	{115}	1130	{115}	----	----	5.87
38	1130	{129}	----	----	----	----	6.54
40	1260	{142}	----	----	----	----	7.25
42	1390	{157}	----	----	----	----	7.99
44	1530	{173}	----	----	----	----	8.77
46	1660	{188}	----	----	----	----	9.59
48	1810	{205}	----	----	----	----	10.4