

Special Profile Independent Wire Rope Core and Rope

特殊異型線鋼心異型線鋼纜



鋼纜直徑 (mm)	拉斷負荷						(參考) 概算 單位質量 kg/m
	無鍍鋅 · 鍍鋅						
	1770 N/mm ² (180 kgf/mm ²)		1960 N/mm ² (200 kgf/mm ²)		2160 N/mm ² (220 kgf/mm ²)		
	kN	{ tf }	kN	{ tf }	kN	{ tf }	
6	30.6	{3.1}	33.8	{3.5}	37	{3.8}	0.184
6.4	34.8	{3.5}	38.5	{3.9}	42	{4.3}	0.209
7	41.6	{4.2}	46.1	{4.7}	50	{5.1}	0.250
8	54.3	{5.5}	60.2	{6.1}	68	{6.9}	0.326
9	68.8	{7.0}	76.1	{7.8}	87	{8.9}	0.413
10	84.9	{8.7}	94.0	{9.6}	103	{10.5}	0.510
11	103	{10.5}	114	{11.6}	128	{12.7}	0.617
12	122	{12.5}	135	{13.8}	149	{15.2}	0.734
13	143	{14.6}	159	{16.2}	175	{17.8}	0.862
14	166	{17.0}	184	{18.8}	203	{20.7}	1.00
15	191	{19.5}	212	{21.6}	234	{23.9}	1.15
16	217	{22.2}	241	{24.5}	267	{27.2}	1.31
18	275	{28.0}	305	{31.1}	340	{34.7}	1.65
20	340	{34.6}	376	{38.3}	418	{42.6}	2.04
22	411	{41.9}	455	{46.4}	505	{51.5}	2.47
24	489	{49.9}	541	{55.2}	601	{61.3}	2.94
26	574	{58.5}	635	{64.8}	705	{71.9}	3.45
28	666	{66.3}	737	{75.1}	818	{83.4}	4.00
30	764	{76.4}	846	{86.3}	939	{95.7}	4.59
32	869	{86.9}	963	{98.2}	1060	{108}	5.22